




Your tool for the modern workplace

Boost your business growth and take your productivity to the next level with the ECOSYS PA3500cx printer. Made for medium to large-size work groups, this A4 colour device is integrated with Kyocera long-life components that help to reduce waste and ensure exceptional levels of reliability.



ECOSYS PA3500cx 

Compact design

Up to 35 pages per minute

Wi-Fi Direct functionality

Specifications

GENERAL

KYOCERA ECOSYS Laser Colour Printer

Operation panel: 5Line display with back light and numeric keypad

Type: Desktop

Engine speed Simplex: Up to 35 pages A4 per minute;

Engine speed Duplex: Up to 17.5 pages A4 per minute.

Resolution: 1200 x 1200 dpi (print),

600 x 600 dpi (scan/copy)

Maximum Life: 600,000 images or 5 years

Warm-up time: Approx. 23 seconds or less

Time to first print: Approx. 5.7 seconds or less

CPU: ARM Cortex-A9 Dual core 1.2GHz

Memory: Standard 1 GB

Standard interfaces: USB 2.0 (Hi-Speed), 2 x USB Host

Interface, Gigabit Ethernet (10BASE-T/100BASE-TX

/1000BASE-T), optional Wireless LAN (IEEE 802.11b/g/n),

1 x eKUIO slot for optional devices other than FAX, Slot for

optional SD Card

Integrated accounting: 100 department codes

Dimensions (W x D x H): Without packaging:

394 x 531.5 x 392.5 mm (without protrusions);

394 x 533 x 392.5 mm (including protrusions);

With packaging: 702 x 567 x 561 mm

Weight: Without packaging:

Approx. 33 kg (with bundled toner)

Approx. 32 kg (without bundled toner)

With packaging: 40 kg

Power source: AC 220 ~ 240 V, 50/60 Hz

Power consumption:

Printing: 496.4W

Ready mode: 11.8 W

Sleep-mode: 0.4 W (default)

Noise (sound pressure level: ISO 7779/ISO 9296):

Operating: 51 dB (LpAm)

Stand-by: 30 dB (LpAm)

Safety standards: TÜV/GS, CE

This unit is manufactured according to ISO 9001 quality

standard and ISO 14001 environmental standard.

PAPER HANDLING

All paper capacities quoted are based on paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions.

Input capacity: Multi-purpose tray: 100 sheets (75 g/m² equivalent), 60–220 g/m². A4, A5, A6, B5, B6, Letter, Legal, Folio, Custom (70 x 140 to 216 x 356 mm), Banner paper up to 1220 mm.

Standard universal paper cassette: 550 sheet with 75 g/m².

60–220 g/m². A4, A5, A6, B5, B6, Letter, Legal,

Folio, Custom (105 x 140 to 216 x 356 mm).

Max. input capacity with options: 2,300 sheets

with 75 g/m².

Duplex: Standard duplex unit 60–163 g/m². A4, A5, A6, B5, Letter, Legal, Custom (140 x 210 mm - 216 x 356 mm).

Output capacity: 250 sheets (Equivalent to 80 g/m²) face down with paper full sensor.

PRINT FUNCTIONS

Controller language: PRESCRIBE

Emulations: PCL6 (Sc/XL), KPDL3 (PostScript 3 compatible), PDF, XPS, Open XPS, TIFF, JPEG, URF, PWG Raster, PCLm

Operating systems: All current Windows operating systems, MAC OS X Version 10.9 or higher, Chrome OS, Linux, as well as other operating systems on request

Fonts/barcodes: 93 outline fonts (PCL6, KPDL3), 4 fonts (Calibri), 4 fonts (Cambria), 1 Bitmap font, 45 types of one-dimensional barcodes, 1 type of two-dimensional barcode (PDF417)

Print features: PDF Direct Print, Internet printing IPP

1.0, E-mail printing, WSD print, secure printing IPP over TLS,

Local and network authentication, Network data encryption

IPsec, HTTPS, LDAP over TLS, SNMPv3,

SMTP over TLS, POP over TLS, Encrypted PDF Direct

Print, TLS 1.3, Secure Boot, Run-time Integrity Check,

Microsoft Universal Print, Printing for Chrome OS

Mobile printing support: KYOCERA Mobile Print app for iOS

and Android, AirPrint, Mopria, Microsoft Universal Print, Wi-Fi

Direct (Opt)

CONSUMABLES

Average continuous toner yield in accordance with ISO 19798

TK-5374K: Black toner 7,000 pages A4

TK-5374Y, TK-5374M, TK-5374C: Yellow, Magenta and Cyan

5,000 pages for A4

Starter toner black 3,500 pages and Yellow, Magenta and

Cyan 2,500 pages A4.

OPTIONS

PF-5150 Paper feeder: Max. 550 sheet with 75 g/m²,

60 - 220 g/m², A5R - Legal, 92.1 x 165.1 (Com6), 114x162

(Youkei2), Max 3 Units

1244/10 Cabinet: for 2-draw configuration

Storage Devices for easy document management:

HD-17 SSD hard disk: 64GB

HD-18 SSD hard disk: 256GB

HD-19 SSD hard disk: 512GB

SECURITY OPTIONS

UG-33 AC: ThinPrint support

UG-35: TPM (Trusted Platform Module)

USB IC Card Reader + Card Authentication Kit (B): Support for various authentication keys available.

CRH 12: Card Reader Holder 12

Optional interface:

IB-37: Wireless LAN (802.11a/b/g/n/ac) with Wi-Fi Direct

IB-50: Gigabit Ethernet 10BASE-T/100BASE-TX/

1000BASE-T

IB-51: Wireless LAN Interface (802.11b/g/n)

WARRANTY

2 years on-site as standard.

WHAT'S IN THE BOX:

Main unit, initial toner, waste toner box, Quick guide, Safety Guide, Operation panel sheet, power supply cord.

ECOSYS stands for ECOlogy, ECONomy and SYStem printing. With their long-life components, ECOSYS devices are designed to maximise durability and minimise the total cost of ownership with regard to maintenance, administration and consumables. The cartridge-free system means that only the toner has to be replaced regularly. The modular design concept allows you to add workflowenhancing functions as required. Integrated system software provides long-term crossnetwork compatibility. KYOCERA's long-life components cost you and the environment less.



* KYOCERA Document Solutions does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged. ** Depending on the country



Brisbane Business Equipment

Unit 1, 747 Fairfield Road,
Yerrongpilly 4105

Ph (07) 32559500

email: sales@bbe.net.au