

Do More with A4

The TASKalfa 308ci is a powerful A4 colour MFP for small to medium sized workgroups in medium to large corporate environment where durable operations and flexible finishing are required. It offers all the functionalities you would expect from a sophisticated MFP - easily accessible touchscreen, various paper handling options including 2,000-sheet large capacity paper feeder and 300-sheet internal finisher with 50-sheet stapling in 3 positions.



Specifications

GENERAL

KYOCERA TASKalfa Laser Colour Multifunctional

HvPAS™ Solution Platform

Operation panel: 177.8 mm (7 inch) full-colour touch panel display, speaker for job notification, 0° - 90° swivel mounted **Engine speed (pages per minute):** Up to 30 pages A4 per minute

Duplex print speed: up to 30 page per minute, A4 Duplex copy speed: 30 page per minute, A4

Resolution: 1200 x 1200 dpi, multibit technology for print quality of up to 9,600 equivalent x 600 dpi (print), 600 x 600 dpi (scan/copy)

Warm-up time: Approx. 20 seconds or less from power on.

Time to first print: Approx. 7.0 / 8.0 seconds or less in b/w/colour

Time to first copy: Approx. 6.4/ 7.8 seconds or less in b/w/colour (Platen Cover)

CPU: ARMCortex-A9 Dual Core 1.2MHz+ARMCortex-M3 100 MHz Memory: Max. 3GB + 32GB or 128GB SSD

Standard interfaces: Standard interface: 2 x USB Host Interface, Gigabit Ethernet (10BaseT/100BaseTX/1000BaseT, IPv6, IPv4,

IPSec, 802.3az support), optional USB 2.0 (High-Speed), Wi-Fi (IEEE 802.11b/g/n), 2 eKUIO slots for optional internal print server, SSD hard disc or fax system, slot for optional SD Card. Integrated accounting: 100 department codes

Dimensions (W x D x H): 550 mm × 507.5 mm × 736.6 mm. Weight: Main unit approx. 49.6 kg.

Power source: AC 220 ~ 240 V, 50/60 Hz

Power consumption Print - mode: 497 Wh

Copy - mode: 497 Wh Low power mode: 38 Wh Ready mode: 69 Wh

Sleep mode: 0.5 Wh Noise (Sound pressure level ISO 7779/ISO 9296)

Operation Mode: 65.4 dB(A) Stand-by: 45dB(A)

Safety standards: TÜV/GS, CE; This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

All paper capacities quoted are based on paper thickness of max. 0.11 mm. Please use paper recommended by Kyocera under normal environmental conditions

Input capacity: Standard universal paper cassette: 500 sheet

100-sheet multi-purpose tray, 60 – 220 g/m², A4, A5, A6, B5, B6, Letter, Legal, Folio, Custom (70 x 148 – 216 x 356 mm). Max. input capacity with options: 3,100 sheets A4

Duplex as standard unit: 60–220 g/m², A4, A5, B5, Letter, Legal Reverse scan document processor as standard: 75 sheets, 50 - 120 g/m², A4, A5, A6, B5, Letter, Legal, Custom (105 x 148 to 216 x 356 mm) Output capacity: 500-sheet-face-down with paper full sensor.

PRINT FUNCTIONS

Controller language: PRESCRIBE II c Emulations: PCL6 (5c/XL), KPDL3 (PostScript 3 compatible), PDF Direct Print, XPS Direct Print.

Operating systems: All current Windows operating systems, MAC OS X Version 10.8 or higher, UNIX LINUX, as well as other operating systems on request. Fonts/barcodes: 93 outline fonts (PCL6), 136 fonts (KPDL 3), 8 fonts (Windows Vista), 1 (Bitmap font), 45 types of one-dimensional barcodes, 1 type of two-dimensional barcode (PDF417).

Print features: Encrypted PDF Direct Print, IPP printing, e-mail printing, WSD print, secure printing via SSL, IPsec, SNMPv3, quick copy, proof and hold, private print, job storage and job management functionality. Mobile printing support: KYOCERA Mobile Print app for iOS and Android, AirPrint, Mopria, Google cloud print.

COPY FUNCTIONS

Max. original size: A4/Legal Continuous copying: 1–999 Zoom range: 25–400% in 1% steps

Preset magnification ratios: 7 Reductions / 5 Enlargements Exposure mode: Auto, manual: 9 steps

Image adjustments: Text + Photo, Photo,

Text, Map, Printed document

Features: Scan-once-copy-many, electronic sort (collate), ID card copy, 2in1, 4in1, auto cassette change, Skip blank page

SCAN FUNCTIONS

Functionality: Scan-to-Email, Scan-to-FTP, Scan-to-SMB, Scan to USB Host, Network TWAIN, WIA, WSD scan **Scan speed:** 40 ipm (300 dpi, A4, b/w), 30 ipm (300 dpi, A4 colour), 17 ipm (300 dpi, A4, b/w) (Duplex), 13 ipm (300 dpi, A4 colour) (Duplex)

Scan resolution: 600, 400, 300, 200 dpi, 256 greyscales per colour

Max. scan size: A4, Legal
Original recognition: Text, photo, text + photo, light text, Searchable PDF with OCR Option
File types: TIFF, PDF, PDF/A, JPEG, XPS, Open XPS,

PDF/A-2a/2B/2U, Encrypted PDF, High compression PDF, PDF/A-1a/b Compression method: MMR /JPEG

Features: Colour scan, integrated address book, Active Directory support, encrypted data transfer, multi send (e-mail, fax, SMB/FTP folder, print) at once, Skip blank page

FAX FUNCTIONS (OPTIONAL)

Compatibility: Super G3 Modem speed: Max. 33.6 kbps Transmission time: Max. 3 seconds (JBIG)

Scanning speed: 2.5 seconds/sheet Address book: 200 entries Scanning density: Normal: 8 dot/mm x 3.85 line/mm (200 x 100 dpi), Fine: 8 dot/mm x 7.7 line/mm (200 x 200 dpi), Superfine 8 dot/mm x 15.4 line/mm (200 x 400 dpi). Ultrafine: 16 dot/

mm x 15.4 line/mm (400 x 400 dpi), Halftone: 256 grey scales Maximum original size: A4/Legal
Compression method: JBIG, MMR, MR, MH Features: Network fax, duplex transmission and reception, encrypted transmission and reception,

polling transmission and reception, broadcast

CONSUMABLES

Average continuous toner yield inaccordance with 5% coverage A4 TK-5199K Toner Kit: Micro fine toner black for 15,000 pages A4 TK-5199C, TK-5199M, TK-5199Y: Micro fine tone cvan, magenta, vellow for 7,000 pages A4

Waste Toner Bottle: WT-5190 Waster Toner Bottle: 44,000 sheets (in accordance with 5% coverage; b/w:colour = 7:3) Staple: SH-10 Staple cartridge: 3 x 5,000 staples for DF-5100

Fax System 11: Super G3 Fax, network fax Paper Handling:

PF-5120: PF-5120 Paper feeder: 500 sheets Fr-3120 : Fr-312

A6, B5, B6, Letter, Legal, Folio, Custom (105 x 148 - 216 x 356 mm). **PF-5140*:** Paper feeder : 2,000 sheets, 60–220 g/m², A4

DT-5100 Document tray: To place originals or USB Keyboard IS -5100 Job separator: 100-sheet internal job separator, 60–220 g/m², A6 - A4/ Legal MT-5100**: 5-bin Mailbox sorter (**AK-5100),

5 bins x 100 sheets A4, $60-163 \text{ g/m}^2$, Main tray 500 sheets A4, $60-220 \text{ g/m}^2$.

DF-5100 Internal Document Finisher. 300 sheets. 60–220 g/m², Stapling up to 50 sheets A4 at 3 positions. * Requires PF-5120

** Bridge unit AK-5100 is required for the use of MT-5100

HD-6 SSD: 32 GB for easy document management

HD-7 SSD: 128 GB for easy document management

Data Security Kit (E) standard for HD-6/HD-7

Nemory Upgrade: MD3-1024, DDR3, 1GB UG-33: ThinPrint support

Optional interface:

USB IC Card Reader + Card Authentication Kit (B): Support for various authentication keys available IC Card Reader Holder 11: To integrate the USB IC Card

IB-50: Gigabit Ethernet: 10BaseT/100BaseTX/1000BaseT.

IB-51: Wireless Lan (802.11b/g/n). IB-35 : Wireless Network Interface

1278 - High Cabinet with stability feet 1279 - High Cabinet with stability feet

The TASKalfa 308ci incorporates extremely durable components that guarantee efficient and reliable operation, to meet the demanding requirements of busy office environments

















Brisbane Business Equipment

Unit 3, 747 Fairfield Road. Yerrongpilly 4105

Ph (07) 32559500

email: admin@bbe.net.au