🔇 КЧОСЕКА

Versatility, Intelligence and Reliability at their best

The TASKalfa 3554ci is the ideal partner for an ever changing business environment featuring reliable performance with reduced maintenance requirements and latest security. Your team can stay focused on their own tasks while this MFP delivers the results they are counting on. The 10.1" touchscreen with our newly designed simple and intuitive user interface will make operating this device as easy as possible.



GENERAL

KYOCERA TASKalfa Laser Colour Multifunctional, HyPAS™ solution platform

Operation panel: 256.5 mm (10.1 inch) full-colour touch panel display, speaker for job notification, 15° - 90° swivel mounted Engine speed: Up to 35/17 pages A4/A3 per minute, Duplex print/copy speed: 35 pages A4 per minute

Resolution: 4800dpi equivalent x 1200dpi (print), 600 × 600dpi (scan/copy)

Warm-up time: 18 seconds or less Time to first print: 5.9/7.7 seconds or less in Mono/Colour Time to first copy: 6.3/8.5 seconds or less in Mono/Colour (DP), Approx. 5.3/7.0 seconds or less in Mono/Colour (Platen)

CPU: ARM A53 (Quad Core) 1.6GHz Memory: Standard 4GB, 32GB SSD, optional 320GB or 1TB Standard interfaces: USB 3.0 (Super-Speed USB), 4 x USB Host Interface, Gigabit Ethernet (10BaseT/100BaseTX/1000BaseT, IPv6, IPv4, IPSec, 802.3az support), optional Wi-Fi (IEEE 802.11a/b/g/n/ ac), 2 eKUIO slots for optional internal print server or for optional $^{\prime\prime\prime}_{\rm r}$ fax system, slot for optional Wireless LAN, Slot for optional SD Card, NFC tag

Dimensions (W × **D** × **H):** $602 \text{ mm} \times 665 \text{ mm} \times 790 \text{ mm}$

Weight: Approx. 90 kg Power source: AC 220–240 V, 50/60 Hz Power consumption: Print Mode: 590W; Copy Mode: 590W;

Ready Mode: 40 W; Sleep Mode: 0.5 W Noise (surface sound pressure level: ISO 7779 measurement distance of 1 meter) Copying/Printing: 69.0 dB(A) in colour

Stand-by mode: 35 dB(A) Safety standards: TÜV/GS, CE. This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

PAPER HANDLING

All paper capacities quoted are based on paper thickness of max. 0.11 mm. Please use paper recommended by Kyocera under normal environmental conditions. Input capacity: Multi-purpose 150 sheets, 52 - 300g/m2, (Banner

136–163 g/m2), A6R - SRA3 (320 x 450 mm), Banner max. 304.8 x 1,220 mm, Standard universal paper cassette: 2 x 500 sheet, 52 -300g/m2, Upper cassette: A6R up to A4R, lower cassette A6R up to SRA3, Max. input capacity with options: 7,150 sheets A4 Duplex: Standard 60 to 256 g/m2. SRA3 to A6R Output capacity: Standard 500 sheets face down, max. 5,000

PRINT FUNCTIONS

controller language: PRESCRIBE

Emulations: PCL6 (PCL5c / PCL-XL), KPDL3 (PostScript 3 compatible), PDF Direct Print, XPS Direct Print and OpenXPS Operating systems: All current Windows operating systems MAC OS X Version 10.9 or higher Unix, Linux, as well as other

operating systems on request Fonts/barcodes: 93 outline fonts (PCL), 136 fonts (KPDL 3), 4 fonts (Calibri), 4 fonts (Cambria), 1 Bitmap font, 45 types of one-dimensional barcodes, 1 type of two-dimensional barcode

(PDF417)

Print features: Encrypted PDF 2.0 Direct Print, IPP printing, e-mail printing, WSD print, secure printing via SSL, IPsec, SNMPv3, quick copy, proof and hold, private print, job storage and job management functionality, Super Resolution Mobile printing support: AirPrint, Mopria, NFC, Direct Wi-Fi (optional), MyPanel and KYOCERA, Mobile Print app for iOS and Android

COPY FUNCTIONS

Max. original size: A3/Ledger

Continuous copying: 1-9,999 Zoom range: 25-400% in 1% steps Preset magnification ratios: 5 Reductions/5 Enlargements Exposure mode: Manual: 17 steps

Image adjustments: Text + Photo, Photo, Text, Diagram/Map Features: Scan-once-copy-many, electronic sort, 2in1, 4in1, image repeat, page numbering, cover mode, booklet copy, interrupt copy, form overlay, margin shift, auto cassette change, skip blank page, ID copy, Handwriting erase and highlight

SCAN FUNCTIONS

Functionality: Scan-to-email, Scan-to-FTP, Scan-to-SMB 3.0, Scan-to-USB Host, Scan-to-box, Network TWAIN, WSD scar (WIA Driver Network)

Scan speed: 200 ipm (300 dpi, A4, duplex, with DP-7160/7170) Scan resolution: 600, 400, 300, 200 dpi, 256 greyscales per colour Max. scan size: A3, Ledger

Original recognition: Text, photo, text + photo, Light Text / Fine Line, optimised for OCR File types: TIFF, PDF, PDF/A, JPEG, Open XPS, Encrypted PDF, High compression PDF, PDF/A-1a/b, PDF/A-2a/b/u, Searchable

PDF (option), MS Office file (option) FAX FUNCTIONS (OPTIONAL)

Compatibility: ITU-T Super G3 Modem speed: Max. 33.6 kbps Transmission time: Less than 3 seconds (JBIG) Scanning speed: 2.0 seconds or less Maximum original size: A3/Ledger, Banner: 1600mm Compression method: JBIG, MMR, MR, MH Features: Network faxing, rotate transmission, rotate reception, encrypted transmission and reception, duplex fax reception, memory reception, mailbox, remote diagnostics, polling transmission and reception, broadcast, Optional Internetfax, dual fax with second fax system 12

CONSUMABLES

verage continuous toner yield in accordance with 5% coverage A4.

TK-8375K Toner Kit: Microfine toner black for 30,000 pages A4 TK-8375C, TK-8375M, TK-8375Y Toner Kits: Microfine toner cyan, magenta, yellow for 20,000 pages A4 Staples: SH-10, 5000 x 3 staples, for BF-730, DF-7100, DF-7120 SH-12, 5000 x 3 staples, for DF-7140 WT-8500: Waste Toner Bottle: 40,000 sheets (in accordance with

5% coverage, b/w : colour = 7:3)

OPTIONS

Fax System 12 Internet Fax Kit (A) AC

Scan Extension Kit (A) AC: Scan to searchable PDF solution (embedded OCR), convert to PDF or MS Office (docx, xlsx, pptx) **DP-7140:** (Reversing), 50 sheets, 45–160 g/m2 (simplex), 50–120 g/m2 (duplex), A5R – A3, Banner up to 1,900 mm

DP-7150: (Reversing), 140 sheets, 35–160 g/m² (simplex), 50–120 g/m² (duplex), A6R–A3, Banner up to 1,900 mm

DP-7160: (one-path duplex scanning), 320 sheets at 50 - 80 g/m², 35–220 g/m² (simplex), 50–220 g/m² (duplex), A6R–A3, Banner up to 1,900 mm

DP-7170: (one-path duplex scanning with ultrasonic sensor), 320 sheets at 50 - 80 g/m², 35-220 g/m² (simplex), 50-220 g/m² (duplex), A6R-A3, Banner up to 1,900mm DT-730(B): Document tray

PF-7120: Side Deck: 3,000 sheets, A4, 60-300 g/m2 PF-7140: 2 x 500 sheets, 52–300 g/m2, A6R–SRA3 PF-7150: 2 x 1,500 sheets, A4, 52–300 g/m2, A4, B5, Letter **DF-7100:** Inner finisher 500 sheets A4, 52–300 g/m2, A6R–SRA3 Stapling up to 50 sheets A4 or 30 sheets A3 at 3 positions DF-7120: 1,000 sheets A4, 52-300 g/m2, A6R-SRA3, Stapling up to 50 sheets A4 or 30 sheets A3 at 3 positions DF-7140: Main tray: 4,000 sheets A4. Sub tray: 200 sheets A4.

52–300 g/m2, A6R–SRA3, Stapling up to 65 sheets A4 or 30 sheets A3 at 3 positions PH-7C/PH-7D: Punch unit for DF-7120 and DF-7140

2-hole/4-hole/Swedish type, 45–300 g/m2, A5R–A3 **MT-730(B):** MT-730(B) Mailbox sorter for DF-7140 7 bins x 100 sheets A4, 50 sheets A3/B4, 60–163 g/m2 **BF-730:** Booklet and tri-folding unit for DF-7140, Half-folding:

52–256 g/m2, A3, B4, A4R, Booklet: Max. 20 sheets (64 pages, 60–90 g/m2), Non-staple folding: Max. 5 sheets (60–90 g/m2) Tri-folding: Tri folding : Max 5 sheets (60–120 g/m2, A4R), Multi tri-folding: 5 sheets (60–90 g/m2), 3 sheets, (91–120 g/m2) JS-7100: 100-sheet internal job separator, 52-300 g/m2, A6R – SRA3

JS-7110: 250-sheet Inner shift tray, 52—300 g/m2, A6R—SRA3 PH-7120: Inner punch unit for inner finisher DF-7100 PH-7130: Inner punch unit for inner finisher DF-7100, Swedish type HD-15: HDD 320 GB HD-16: HDD 1 TB

NK-7120: NK-7120 Numeric keypad

UG-33 AC: ThinPrint support


UG-34 AC: Emulation (IBM Proprinter/EPSON LQ-850/ LinePrinter)

USB IC Card Reader + Card Authentication Kit (B) AC IB-37: Wireless Network Interface (USB : 5GHz/2.4GHz) IB-38: Wireless Network Interface (USB : 2.4GHz) IB-50: GB-Ethernet board 10 BaseT/100 BaseTX/1.000 BaseT

IB-51: Wireless LAN Interface (802.11b/g/n) Platen cover Type (E) CB-7200W: Wooden cabinet

CB-7210M: Metal cabinet

HVPAS



🚺 KYOCERa

mopria

Authorised Dealer



Brisbane Business Equipment

Unit 1, 747 Fairfield Road, Yerrongpilly 4105 Ph (07) 32559500

email: sales@bbe.net.au

Kyocera Document Solutions does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at me of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged