

> PRINT > COPY > SCAN > FAX

TASKalfa 7052ci

COLOUR MULTIFUNCTIONAL FOR A₃ FORMAT

THE INTELLIGENT BUSINESS PLATFORM.



Our new TASKalfa 7052ci MFD is the perfect choice for all demanding workgroups and production offices. From its fast overall performance to the advanced paper handling options and a maximum paper capacity of 7,650 sheets, there's not much left to be desired. Print quality is astounding: The TASKalfa 7052ci prints at 1,200 x 1,200 dpi, delivering highly detailed results even at highest print speeds. The new and advanced toner enlarges the colour gamut, producing the most vivid and vibrant colours. Additionally, the redesigned 9" touch panel makes accessing all features very intuitive and easy to use.

- > Up to 70 A4 ppm in b/w, up to 65 A4 ppm in colour
- > Outstanding image quality due to advanced colour technology
- > Standard print resolution of 1,200 x 1,200 dpi
- > State-of-the-art 4.5 GB RAM + 8 GB SSD + 320 GB HDD
- > Long-life components reduce waste and provide exceptional efficiency and reliability
- > Individual paper handling options, including booklet and tri-folding
- > Optional Fiery Controller for highest productivity and colour quality



TASKalfa 7052ci **GENERAL**

Technology

KYOCERA Laser Colour, HyPAS™ solution platform Engine speed (pages per minute): Up to 65/32 A4/A3 in colour, up to 70/35 A4/A3 in b/w

Resolution: 1,200 x 1,200 dpi, 2-bit depth for print quality of 4,800 dpi equivalent x 1,200 dpi

Warm-up time from power on

Approx. 44 seconds or less

Time to first page: Approx. 5.4 sec. or less in b/w; 6.2 sec.

CPU: Freescale QorlQ T1042 Quad Core 1.2 GHz Memory: 4.5 GB RAM + 8 GB SSD + 320 GB HDD

Standard interfaces: USB 2.0 (Hi-speed) x/i, USB Host 2.0. Fast Ethernet 10BaseT/100BaseTX/1000BaseT, slot for optional print server, slot for optional SD, SDHC card, slot

Dimensions (W x D x H) - main unit

750 x 822 x 1234 mm (Include DP and Operation Panel)

Weight: Main unit approx, 182 kg Power source: AC 220 V ~ 240 V, 50/60 Hz

Power consumption

Printing: 1,360 W (in colour), 1,310 W (in b/w)

Ready mode: 120 W Sleep mode: 1 W or less

Noise (sound pressure level ISO 7779/ISO 9296)

Printing: 75 dB(A) (Lwad), 53.6 dB(A) LpA (in b/w) Ready mode: 58 dB(A) (Lwad)

Safety standards: IEC60950-1, IEC60825-1; This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard. RoHS compatibility

PAPER HANDLING

All paper capacities quoted are based on paper thickness of max, 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions.

Input capacity: 150-sheet multi-purpose tray, 60 - 300 g/m² (banner 135 – 165 g/m²), A6R – 305 x 457 mm, banner max. 305 x 1,220 mm; 2x 1,500-sheet high-capacity paper deck, 60 - 256 g/m². A4. B5: 2x 500-sheet universal paper cassette, 60 - 256 g/m², A5R - 305 x 457 mm incl. custom

Max. input capacity with options: 7,650 sheets A4 Document processor: (one-path duplex scanning) 270 sheets; 35 – 220 g/m² (simplex), 50 – 220 g/m² (duplex); A6R – Banner up to 2.200 mm

Duplex unit: Duplex as standard supports A5R -305 x 457 mm, 60 - 256 g/m²

Output capacity: Standard job separator tray 70 sheets, optional copy tray (D): upper 100 sheets, lower 250 sheets Max. optional output capacity 4,300 sheets

PRINT FUNCTIONS

Controller language: PRESCRIBE

Emulations: PCL6 (PCL5c/PCL-XL), KPDL3 (PostScript 3 compatible), PDF Direct Print, XPS Direct Print and OpenXPS Operating systems: All current Windows operating systems, Mac OS X Version 10.8 or higher, UNIX, LINUX, as well as other operating systems on request.

Fonts/barcodes: 93 outline fonts (PCL), 136 fonts (KPDL3). 8 fonts (Windows Vista), 1 Bitmap font, 45 types of one-dimensional barcodes plus two-dimensional barcode (PDF-417)

Print features: Encrypted PDF Direct Print, IPP printing. e-mail printing, WSD print, secure printing via SSL, IPsec, SNMPv3, quick copy, proof and hold, Private Print, job storage and job management functionality

Mobile printing support: KYOCERA Mobile Print app for iOS and Android, AirPrint, Mopria, NFC, Direct Wi-Fi,

COPY FUNCTIONS

Max. original size: A3 Continuous copying: 1 - 9999 Zoom range: 25 - 400% in 1% steps Preset magnification ratios: 5R/5E

Digital features: Scan once copy many, electronic sort, 2-in-1 and 4-in-1 function, image repeat copy, page numbering, cover mode, booklet copy, interrupt copy, form overlay, stamp function and skip-blank-page function.

Exposure mode: Auto, manual: 16 steps Image adjustments: Text + photo, text, photo, map

SCAN FUNCTIONS

Functionality: Scan-to-email, Scan-to-FTP, Scan-to-SMB, Scan-to-USB Host, Scan-to-box, Network TWAIN, WSD scan Scan speed: (A4, 300 dpi, Dual Scan) 220 images per minute

Scan resolution: 600 x 600 dpi, 400 x 400 dpi, 300 x 300 dpi, 200 x 400 dpi, 200 x 200 dpi, 200 x 100 dpi (24 bit)

Max. scan size: A3, Banner up to 2.200 mm Original recognition: Text, photo, text + photo, optimised

File types: PDF (high compression, encrypted, PDF/A), Searchable PDF (OCR), JPEG, TIFF, XPS, OpenXPS

FAX FUNCTIONS (OPTIONAL)

Compatibility: ITU-T Super G3 Modem speed: Max. 33.6 kbps

Transmission speed: Max. 3 seconds (JBIG)

Fax resolution:

Normal: 200 x 100 dpi Fine: 200 x 200 dpi Superfine: 200 x 400 dpi Ultrafine: 400 x 400 dpi 600 x 600 dpi

Maximum original size: A3, Banner up to 1,600 mm

Compression method: IBIG, MMR, MR, MH Features: Opt. Internet-fax, network faxing, rotate transmis-

sion, rotate reception, duplex fax reception, memory reception, mailbox, remote diagnostics, dual fax with second fax system 12

TK-8729 Toner-Kit: Toner Black for 70,000 pages

TK-8729 CIMIY Toner-Kits: Toner cyan, magenta, yellow for 30.000 pages Average continuous toner yield in accordance with 5% coverage A4.

WT-861 Waste Toner Bottle: 150,000 sheets (in accordance with 5% coverage. Colour: b/w = 6:4)

Staple cartridge: SH-10 for BF-730, SH-12 for DF-7110

Fax System 12

Internet Fax Kit (A)

Printing System 16: Fiery Controller

Printing System Interface Kit 15: Interface board for Fiery Paper handling

PF-730(B) Paper feeder

2x 500 sheets, 60 - 256 g/m², A5R - 305 x 457 mm, folio

PF-740(B) Paper feeder

2x 1,500 sheets, 60 – 256 g/m², A4, B5, letter

PF-7130 Paper feeder

B5 - 305 x 457 mm

500 sheets, 60 – 256 g/m², A5R – 305 x 457 mm

PF-7120 A4 side deck: 3,000 sheets, 60 - 256 g/m2, A4, B5 DF-7110 Document finisher

Main tray: max. 4,000 sheets A4 (3,000 sheets with BF-730 attachment); max. 60 – 300 g/m²; max. B5R – 305 x 457 mm Sub-tray: 200 sheets A4; 60 - 300 g/m2; A6R - 305 x 457 mm Sub-tray (top): 100 sheets; 60 - 300 g/m2; A6R - A4 Stapling up to 65 sheets A4 or 30 sheets A3 at 3 positions,

PH-7C/PH-7D Punch unit for DF-7110

2-hole/4-hole/Swedish type, 60 - 300 g/m², A5R - A3

MT-730(B) Mailbox sorter for DF-7110

7 bins x 100 sheets A4, 50 sheets A3/B4, 60 – 163 g/m² BF-730 Booklet and tri-folding unit for DF-7110

Half folding: 60 - 256 g/m2, A3, B4, A4R; Booklet: max. 16 sheets (64 pages, 60 - 90 g/m2); Non-staple folding: max. 5 sheets (60 – 90 g/m²); Tri-folding: 60 – 105 g/m², A4R Multi tri-folding: 5 sheets (60 - 90 g/m²), 3 sheets

Copy tray (D): upper tray 100 sheets, lower tray 250 sheets Banner Guide (A)

Banner paper feeding guide, up to 10 sheets

Security

Data Security Kit (E): In line with ISO 15408 (Common

Criteria) with security level EAL3

USB IC Card Reader: Card Authentication Kit (B) Numeric

Keybordholder 10

UG-33 AC: ThinPrint support

UG-34 AC: Emulation (IBM Proprinter/EPSON LO-850)

Optional interface

IB-35 : Direct Wi-Fi Interface

IB-50: Gigabit-Ethernet board 10BaseT/100BaseTX/1000BaseT

IB-51: Wireless Lan Interface



















Brisbane Business Equipment

Unit 3, 747 Fairfield Road, Yerrongpilly 4105

Ph (07) 32559500

email: admin@bbe.net.au

